

Cleaning and Disinfecting of Sxnnnn Switches Application Note

VIEWING WINDOW MATERIAL

The viewing window of the Sxnnnn keyswitches is made from Plexiglas® HW55 (acrylic glass). This material is a copolymer of methyl methacrylate (MMA) with comonomer constituents.

In addition to the common characteristics of acrylic glass this material has the following properties:

- high degree of scratch resistance
- higher degree of thermal form consistency
- improved resistance against tension fractures
- optimized transparency and clarity

CLEANING

Dust does not adhere to the non-porous surface of the viewing window. Dusty switches should be wiped with damp, soft, lint-free cloth. Do not dry rub. For thorough cleaning a small amount of common household detergent may be added to the water or a non-abrasive cleaner (e.g. anti-static plastic cleaner) may be used. Damp microfibre cloths are well suited for streak-free cleaning. Grimy and oily surfaces may be cleaned using benzene-free petroleum ether.

CHEMICAL RESISTANCE

The Sxnnnn switches are resistant to

- weak acids
- weak caustic solutions
- fats
- oils
- turpentine

The switches surfaces are NOT resistant to

- concentrated acids
- oxidizing acids
- concentrated caustic solutions
- alcohols

DISINFECTION

Wipe the switches frequently with a damp, lint-free cloth and warm to hot water.



[E³] Engstler Elektronik Entwicklung GmbH Auweg 27 ● 63920 Grossheubach ● Germany

WWW.E3-KEYS.COM

© 2020-2024 Copyright [E³] Engstler Elektronik Entwicklung GmbH. All rights reserved.

 $[E^3]$, The Third EvolutionTM and Legacy ModeTM are trademarks of $[E^3]$. The Keys to IntelligenceTM is a trademark of I/O Universal Technologies, Inc. used with permission. All other trademarks are property of their respective owners.

No part of this publication may be copied, photocopied, reproduced, translated or reduced to any electronic medium or machine-readable form without the expressed written consent of [E³] Engstler Elektronik Entwicklung GmbH.